

POWER ARROW
AC 11KW | 22KW



FEATURES

- + TWO AC charging outlet
 - TYPE 2
- + ONE cabinet
 - 11 KW
 - 22 KW
- + HIGH efficiency
Maximum efficiency > 95,6%
- + IP 54
- + OCPP 1.6 JSON
- + WALL or STANDING MODEL

APPLICATIONS



Highway
Service



Parking
Lots



Fuel
Station



Commercial
Fleet



EV
Infrastructure

PRODUCT SPECS

MODEL	AC-D-P11 SERIES	AC-D-P22 SERIES
Capacity Dimension Net Weight	2 x 11kW 1200 x 410 x 220 mm excluding plug and cable 63KG	2x 22kW 63KG
Input Voltage Phase Frequency Power Factor THD	400 VAC 15% 3-phase + N + PE 50HZ - 60 HZ >0.99 @ Full load <5% @ 50% load	
Output Outlets Type Nominal Current Smart Power Control THD	2 Type 2 sockets AC 32A Max Yes >95.6%	AC 63A Max
Operational Environment Temperature Altitude Humidity Storage temperature IP level	- 25° to 60° (45° start to derating) < 2000 m (derating operation to 3500 m) < 95% -40° to 70° IP 54	
OTA Communication Payment Network interface Communication Protocol	RFID 3G/4G (Optional) OCCP 1.6 JSON	
Warranty	2 years	